Date:	Lot No		
Owner:			
Property Address:			
Email Address:	Phone 1	Phone Number:	
The following items are required to be co	onsidered for approval:		
location of the fence, fence dimer ☐ Fence styles and colors are limited ☐ Fences may not be built in either from the utility company(s). ☐ Fences are not permitted to be pla ☐ It is required that the fence be bui ☐ The fence must be constructed 10 corner lot, fence must be 10 feet the	Right of Ways or General Utility E aced in a drainage easement without alt on the rear and side yards with confect from the front corner of the ho from curb on the side facing the roa	ze. asements without proper approval t written approval from the County. consistent fencing type. buse that is closest to the street. On a	
Select Fence Type from below:			
Option 1 (6' Wood)	Option 2 (6' Wood)	Option 3 (6' Wood)	
- Individual scare			
Option 4 (4' iron or Aluminum limited to black)	Option 5 (5' Iron or Aluminum, limited to black)	Option 6 (6' Vinyl)	

Option 7 (4' Vinyl picket)



APPROVED WOOD FENCE COLORS



WoodScapes* Exterior Acrylic Solid Color Stain • Penetrates for exceptional resistance

- Penetrates for exceptional resistance to peeling and mildew
- Thick formula for uniform finish with great coverage
- · Excellent color retention
- Exceptional prevention of tannin stains in cedar and redwood.
- . Low temperature application to 35° F
- Recommended for Siding, Trim and Fence applications



SW6258 Tricorn Black

Color Number: SW6258 Color Display Locator: 251-C1 Color Family Name: Neutrals



WoodScapes* Exterior Acrylic Solid Color Stain

- Penetrates for exceptional resistance to peeling and mildew
- Thick formula for uniform finish with great coverage
- · Excellent color retention
- Exceptional prevention of tannin stains in cedar and redwood.
- Low temperature application to 35° F
- Recommended for Siding, Trim and Fence applications

SW7006 Extra White

Color Number: SW7006 Color Display Locator: 257-C1 Color Family Name: White and Pastel



WoodScapes* Exterior Acrylic Solid Color Stain

- Penetrates for exceptional resistance to peeling and mildew
- Thick formula for uniform finish with great coverage
- · Excellent color retention
- Exceptional prevention of tannin stains in cedar and redwood.
- Low temperature application to 35° F
- Recommended for Siding, Trim and Fence applications



SW9170 Acier

Color Number: SW9170 Color Display Locator: 244-C4 Color Family Name: Neutrals

APPROVED WOOD FENCE COLORS (Cont.)



SuperDeck Exterior Waterborne Semi-Solid Color Stain • Damp Application - Efficiency can be

- Damp Application Efficiency can be applied to damp wood, so most jobs can be finished in a single day.
- This coating contains agents that inhibit the growth of mildew on the surface of this coating



SW2808 Rookwood Dark Brown

Color Number: SW2808 Color Display Locator: 310-C2 Color Family Name: Historic Exterior



SuperDeck Exterior Waterborne Semi-Solid Color Stain

- Damp Application Efficiency can be applied to damp wood, so most jobs can be finished in a single day.
- This coating contains agents that inhibit the growth of mildew on the surface of this coating



SW7515 Homestead Brown

Color Number: SW7515 Color Display Locator: 277-C5 Color Family Name: CIC/Timeless

APPROVED VINYL FENCE COLORS

Circle Choice



Tan


Clay

Wood Grain


Wood Grain Gray White

Owner	er Signature	Print Name
by the consid	er is responsible for contacting the County regarding any per Design Committee is for conformance with design concerderation only. Design Committee is not responsible for the ruction or modifications, compliance with building codes,	epts and design guidelines from an overall aesthetic estructural integrity or soundness of approved
Comm valid f	er has read and understands that contractor and homeowner nunity Design Guidelines. Owner acknowledges once approval for 6 months after receipt of approval. Fences should be plicable.	lication is approved by the Design Committee, it is
proper	er hereby authorizes the Association and/or members of the erty for purposes of reviewing information provided and for letion of the project, and/or upon expiration of approval.	or inspecting the project during execution, upon
The su Design Construction not conthe pro	ubmittal of this application does not constitute approval of a Committee's decision will be supplied within 30 days a cruction must not begin until the Committee has approved constitute an approval, ratification, or endorsement of the queroposed improvements and neither the Design Committee is in the plans, specifications, or improvements.	fter receipt of all required information. the plans in writing. Approval of application shall uality or architectural or engineering soundness or
	A picture of the installed painted/stained fence must be following completion.	submitted to the Design Committee within 30 days
	Fence must be installed by a professional fencing contra	actor hired by the Owner, at Owner's cost.
	Alley Setback: All fences must be set a minimum of 5'	from the alley.
	The fence must be constructed 10 feet from the front co corner lot, fence must be 10 feet from curb on the side f	
	ences are required to be installed a minimum of three (3) inches off the ground and not impede surface trainage.	
	Fences are required to be level and step with grade, such	that top rail is level. Do not slope with grade
	Homeowner and contractor are responsible for locating construction. Properties may vary, but typically a 5' util property lines. A County encroachment permit is require	ity easement exists along alleys and street side
	the replacement cost of the fence will be at the homeowner	1 1

OPTION 1: 6' HIGH PRIVACY FENCE



OUTSIDE - FACING STREET OR NEIGHBOR



INSIDE – FACING YARD

EXAMPLES OF APPROVED CAPS



Two-piece chamfered cap

CONSTRUCTION NOTES

HEIGHT: 6' maximum height

POST: 6x6 with post caps

CAPS: Two-piece chamfered caps or

Newport High Pyramid Post Cap

MATERIAL: Pressure-treated wood


CONSTRUCTION: Structure on inside of fence 6" wide vertical boards 1x6 top rail with horizontal cap intermediate supports or structure on inside of fence spacing and additional supports by contractor fence must be level and step with grade and cannot be sloped


FINISH: Paint or stain within 90 days of construction



Newport High Pyramid Cap


OPTION 2: 6' HIGH PRIVACY FENCE YARD SIDE GATE (MAX SIZE DBL GATE 5') FOR REVEW FOR REVEW PLAN 1/4" = 1'-0"





Rear Yard Fence within the Alley Yard, Front Façade Zone or Side Street Façade Zone


- Maximum Height 6' above grade
- Maximum Opacity above 4' high is 50%, unless otherwise indicated



Rear Yard Fence within the Alley Yard, Front Façade Zone or Side Street Façade Zone


- . Maximum Height 6' above grade
- . Maximum Opacity above 4' high is 50%, unless otherwise indicated


RENDERING



YARD SIDE







Rear Yard Fence within the Alley Yard, Front Façade Zone or Side Street Façade Zone


- . Maximum Height 6' above grade
- . Maximum Opacity above 4' high is 50%, unless otherwise indicated

2 STREET SIDE 1/4" = 1'-0"




Rear Yard Fence within the Alley Yard, Front Façade Zone or Side Street Façade Zone

- . Maximum Height 6' above grade
- . Maximum Opacity above 4' high is 50%, unless otherwise indicated



4 PENDERING



YARD SIDE

